

CUCIMAX



## **CBTEA\_V1 : ROUND BRATT PANS PRESSURE WITH MIXER, ELECTRIC TYPE "FIREX TOUCH CONTROL"**

### **Constructive Features**

Cooking vessel in stainless steel AISI 304 (bottom thickness 12 mm and wall thickness 3 mm). Vessel with electric tilting on front part.

Lid in stainless steel AISI 304 (thickness 20/10), with double cover, with ergonomic handle, reinforced with locking system at 4 points on sliding shafts and lever type control bolts with blocking of opening under pressure. Alimentary silicone gummy gasket with only one jointing point. Balanced by means of gas springs.

Self-supporting frame in stainless steel AISI 304 (thickness 30-40/10)

Outer cover in stainless steel AISI 304, fine satin finish (thickness 12-15/10)

Adjustable feet in stainless steel AISI 304 to ensure levelling, with removable cover for cleaning operations.

Fast accessibility to the main functional parts ( electronic card, fuses, thermostats...) only removing the frontal panels

Protection level IPX5.

### **Functional Features**

#### **General**

Heating by means of armoured elements in INCOLOY-800 alloy controlled by electronic board.

Temperature control by system with two probes (product/bottom)

Pressure cooking with automatic system for eliminating air from the cooking container (for cooking with saturated steam) and automatic steam condensation after cooking to allow fast and safe lid opening without steam dispersion in the room.

Automatic mixing device with three arms and PTFE scrapers, completely removable to make cleaning easier, with regulation directly from the control panel according to the product to be processed.

Electronic control by means of multifunctional keyboard with Touch Screen 7" and easy and clear messages.

USB connection to download HACCP data, update the software and load cooking programs.

Ability to interrogate the machine using communication protocol MODBUS over RS485 serial interface.

Connection for power economizer

#### **Panel Board**

#### **Functions**

- ON/OFF switch
- resistive 7" touch screen.
- keys to turn on/off the mixer and move basin.

- selection of 8 different cooking modes, with working temperature setting.
- possibility of cooking with tilted basin (up to 15°)
- cooking type and time setting.
- cooking in "Manual" mode.
- cooking in "Program" mode.
- creating and editing multiphase cooking programs, setting for each phase: cooking type; cooking parameters (temperature and time); mixer settings and possibility to insert text messages.
- speed setting/adjustment (clockwise and counterclockwise) rotation times and mixer pause times.
- possibility to activate mixer at minimum speed during tank tilting to facilitate product pouring.
- tank water load setting (hot up to 90° C/cold) with automatic liter measurements.
- control for tilting and return of cooking tank from Touch Screen or keyboard.
- delayed cooking setting with date, time, and programming cycle.
- language settings touch Screen.
- input of different units of measurement (° C/° F; Liters/gallons; etc).

#### **Display/Signal**

- display type of cooking, temperature probes used and set temperature.
- heating operating visual alarm
- time to end of cycle display
- tank pressure display.
- reporting lid locking and condensing time during cooking under pressure.
- display tank out of position for cooking.
- audible/visible warning of mixer program start.
- signaling tap position, managing water in the tank.
- signal of lid and cock position during vat tilting.
- thermostat intervention safety signaling.
- self-diagnostics.

#### **Safety System**

- emergency button
- blocking of heating for excess of temperature with manual resettable safety thermostat
- mechanical lid opening lock with tank under pressure.
- lid safety valve .
- heating interruption during vat tilting

# Mod: CBTE180A\_V1

Dato / Data	U.M.	Valore / Value
Potenza Elettrica Electric Power	kW	26.40
Tensione Voltage	Volt	380-415V 3N ~ 50/60Hz
IPX		5
Pressione Cottura Cooking pressure	bar	0,2
Diametro vasca Vat diameter	mm	900
Altezza vasca Cooking vessel depth	mm	370
Superf. Fondo Cooking vessel surf.	dmq	63
Capacit� Totale Overall Capacity	Lt	235
Capacit� Utile Useful Capacity	Lt	190
Dim. Esterne (A) External Dimens. (A)	mm	1.655
Dim. Esterne (B) External Dimens. (B)	mm	1.500
Dim. Esterne (H = Piano Lavoro) External Dimens. (H = working top)	mm	950
Dim. Esterne (H2 = Coperchio aperto) External Dimens. (H2 = lid opened)	mm	2.360