

OTHER INFORMATION

INSTALLATION SPECIFICATIONS

Installation phases require 2 - 4 hours.

All oven parts can fit through a standard 36" x 80" door.

All electrical and ventilation hook-ups are at the customer's responsibility and expense.

As for ventilation requirements, a specialist is required.

A certified electrician is required on site during installation phases.

ELECTRICAL REQUIREMENTS

Voltage	208 V
Phase	3
Frequency	60 Hz
Current Draw	PHP4 = 21 A / PHP6L = 27,5 A
Supply	PHP4 = 7,5 kW / PHP6L = 9,9 kW
Breakers	PHP4 = 30 A / PHP6L = 40 A

- The plug, cable and receptacle are not included.
- The oven's connections must be made by an electrician on the installation day.

SHIPPING INFORMATION

Model	Packaging width	Packaging lenght	Packaging Height	Packaging weight with hood	Packaging weight with small hood
Pyrals HP 4	47,2" 120 cm	51,2" 130 cm	28,3" 72 cm	421,10 lb 191 kg	390,20 lb 177 kg
Pyrals HP 4+4*	47,2" 120 cm	51,2" 130 cm	28,3" 72 cm	811,30 lb 368 kg	780,40 lb 354 kg
Pyrals HP 4+4+4 *	47,2" 120 cm	51,2" 130 cm	28,3" 72 cm	1201,50 lb 545 kg	1170,60 lb 531 kg
Pyrals HP 6L	47,2" 120 cm	63" 160 cm	28,3" 72 cm	513,70 lb 233 kg	474 lb 215 kg
Pyrals HP 6L + 6L*	47,2" 120 cm	63" 160 cm	28,3" 72 cm	987,70 lb 448 kg	948 lb 430 kg
Pyrals HP 6L + 6L + 6L*	47,2" 120 cm	63" 160 cm	28,3" 72 cm	1461,70 lb 663 kg	1422 lb 645 kg
Stand 4 for 1 oven	36,6" 93 cm	44,9" 114 cm	6,9" 17,5 cm	99,20 lb 45 kg	99,20 lb 45 kg
Stand 4 for 2 ovens	36,6" 93 cm	44,9" 114 cm	6,9" 17,5 cm	94,80 lb 43 kg	94,80 lb 43 kg
Stand 4 for 3 ovens	36,6" 93 cm	44,9" 114 cm	6,9" 17,5 cm	90,40 lb 41 kg	90,40 lb 41 kg
Stand 6L for 1 oven	36,6" 93 cm	59" 150 cm	6,9" 17,5 cm	112,40 lb 51 kg	112,40 lb 51 kg
Stand 6L for 2 ovens	36,6" 93 cm	59" 150 cm	6,9" 17,5 cm	108 lb 49 kg	108 lb 49 kg
Stand 6L for 3 ovens	36,6" 93 cm	59" 150 cm	6,9" 17,5 cm	103,60 lb 47 kg	103,60 lb 47 kg
Hood 4	48" 122 cm	48" 122 cm	22,25" 56,5 cm	141,10 lb 64 kg	
Hood 6L	61,8" 157 cm	48" 122 cm	22,25" 56,5 cm	169,80 lb 77 kg	

* Shipped in 2/3 separate boxes