
Easy Install Pre-Rinse Unit

Architect/Engineering Specifications:

Single hole deck mount mixing faucet with polished chrome plated brass body, add-on faucet with compression cartridge with spring check and lever handle, 12" swing nozzle with stream regulator outlet, 24" riser, 44" flexible stainless steel hose with heat resistant handle, 1.42 GPM spray valve, compression cartridges with spring checks, lever handles, 18" flexible stainless steel supply hoses with 1/2" NPSM / 5/8" O.D. compression connections, 6" adjustable wall bracket, spray valve holder, accessory tee and overhead spring. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. EPAct 2005 compliant.





Features & Benefits:

- Single hole deck mount mixing faucet w/ polished chrome plated brass body
- EasyInstall add-on faucet w/ polished chrome plated brass body
- 12" swing nozzle w/ stream regulator outlet
- 24" rigid riser
- 44" flexible stainless steel hose w/ heat resistant gray handle and hold down ring
- 1.42 GPM spray valve
- Quarter-Turn Eterna cartridges w/ spring checks to prevent cross flow of water
- Lever handles w/ color coded indexes
- 18" flexible stainless steel supply hoses w/ 1/2" NPSM / 5/8" O.D. compression connections
- 6" adjustable wall bracket
- Tee for accessory fittings
- Material: Polished chrome plated brass body, & tubular nozzle, add-on faucet body, riser & spray valve, stainless steel hose and chrome plated metal handles

Optional Add-On Faucet Outlets (Series 1 / VR Series 6)

GPM	Aerated	VR Aerated
1.0	□ B-0199-01-F10	□ B-0199-06-F10
1.5	□ B-0199-01-WS	□ B-0199-06-WS
2.2	□ B-0199-01	□ B-0199-06

T&S BRASS AND BRONZE WORKS, INC.

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- EPAct 2005 (PRSV)

Warranty: Three Year (Limited)

Performance Data:

Pressure: 20 - 125 psiTemperature: 40 °F - 140 °F

Flow Rate:

Spray Valve: 1.42 GPM @ 60 psi Add-On Faucet: 5.57 GPM @ 60 psi

Optional Cartridges With Checks

- $\hfill \square$ Quarter-Turn Cerama w/ Check Valve
- □ Quarter-Turn Eterna w/ Spring Check (Standard)

Optional Handles	Optional Pre-Rinse Spray Valves
□ 4" Wrist Action□ Lever (Standard)□ 4-Arm	 □ B-0107 (1.42 GPM) (Standard) □ B-0107-C (0.65 GPM) □ B-0107-J (1.07 GPM) □ B-0108 (1.07 GPM) □ B-0108-C (0.65 GPM)









