

Faucets and Spray Valve Assemblies

TAG:


B-0175-06


Faucet with Swing Nozzle and Spray Unit

Architect/Engineering Specifications:

8" wall mount mixing faucet with polished chrome plated brass body, add-on faucet with compression cartridge and lever handle, 8" swing nozzle with stream regulator outlet, 68" flexible stainless steel hose with heat resistant handle, 90° swivel adapter arm, 1.42 GPM angled spray valve, compression cartridges with spring checks, lever handles, 1/2" NPT female inlets and hose hanger hook. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. EPAct 2005 compliant.

Job Name		
Model Specified	Quantity	
Variations Specified		
Date		







Features & Benefits:

- 8" wall mount mixing faucet w/ polished chrome plated brass body
- EasyInstall add-on faucet w/ polished chrome plated brass body
- 8" swing nozzle w/ stream regulator outlet, Series 1
- 68" flexible stainless steel hose with heat resistant gray handle and hold down ring
- 90° swivel adapter arm
- 1.42 GPM angled spray valve
- Quarter-turn Eterna compression cartridges w/ spring checks to prevent cross flow of water
- · Lever handles w/ color coded indexes
- 1/2" NPT female eccentric inlets with Ø 2" flanges
- Adjustable centers from 7 3/4" to 8 1/4"
- · Hose hanger hook
- Material: Polished chrome plated brass body, add-on faucet, hanger hook, tubular nozzle, swivel arm and spray valve, stainless steel hose & chrome plated metal handles

Optional Add-On Faucet Outlets (Series 1 / VR Series 6)

GPM	Aerated	VR Aerated (VR Laminar)
1.0	□ B-0199-01-F10	□ B-0199-06-F10
1.5	□ B-0199-01-WS	□ B-0199-06-WS
2.2	□ B-0199-01	□ B-0199-06

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- EPAct 2005 (PRSV)

Warranty: One Year (Limited)



Performance Data:

- Pressure: 20 125 psiTemperature: 40°F 140°F
- · Flow Rate:

Spray Valve: 1.42 GPM @ 60 psi Add-On Faucet: 9.73 GPM @ 60 psi

Optional Pre-Rinse Spray Valves

□ B-0107 (1.42 GPM)
□ B-0107-C (0.65 GPM)
□ B-0107-J (1.07 GPM)

□ B-0108 (1.07 GPM)
□ B-0107-C (0.65 GPM)

Optional Cartridges With Checks

□ Quarter-Turn Cerama w/ Check Valve□ Quarter-Turn Eterna w/ Spring Check (Standard)

T&S BRASS AND BRONZE WORKS, INC.









Date: 02/28/18

Optional Handles

☐ 4" Wrist Action

□ 4-Arm

□ Lever (Standard)