

# Electronic Sensor Faucet

TAG:

### **Architect/Engineering Specifications:**

4" deck mount electronic sensor faucet with polished chrome plated brass body with integral spout, 1.5 GPM vandal resistant aerator, AC/DC control module with internal flow control setting switches, temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements.







# Features & Benefits:

- 4" deck mount faucet w/ polished chrome plated brass body with integral spout
- 1.5 GPM vandal resistant aerator, Series 8 (B-0199-08-WS)
- Water resistant control module w/ internal flow control switches for adjusting auto time out & shut off delay settings
- Optional auto flush feature flows water for 30 seconds after every
  12 inactive hours
- Plug in AC transformer or (4) AA battery (DC) power options
- Mechanical temperature mixing valve with integral check valves
- 18" flexible stainless steel supply hoses with 3/8" compression connections
- Low battery LED indicator light
- Material: Polished chrome plated brass body

#### **Product Compliance:**

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- UL 1951

Warranty: Three Year (Limited)

#### Performance Data:

Pressure: 20 - 125 psi

Temperature: 40 °F - 140 °F

• Flow Rate: 1.5 GPM @ 60 psi







## Optional Outlets (Series 3 / VR Series 8)

GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)
0.35	N/A	□ B-0199-03-N035	N/A	□ B-0199-08-N035
0.5	N/A	□ B-0199-03-N05	N/A	□ B-0199-08-N05
1.0	N/A	N/A	N/A	□ B-0199-08-LF10
1.2	□ B-0199-03-F12	N/A	□ B-0199-08-F12	N/A
1.5	□ B-0199-03-WS	N/A	□ Standard	□ B-0199-08-LF15
2.2	□ B-0199-03	□ B-0199-26	□ B-0199-08	□ B-0199-28







T&S BRASS AND BRONZE WORKS, INC.

